

Main Parameter of **WA67Y / WF67Y / WA67K** Torsion
Synchronization Press Brake Machine

No.	Model	Nominal Pressure (kn)	Max Working Length (mm)	Distance Between Uprights (mm)	Open Height (mm)	Throat Depth (mm)	Stroke (mm)	Stocke adjustment (mm)	Worktable Height (mm)	Main Motor (kw)	Hydraulic Oil Flow Rate (L)	Speed (mm/s)			Dimensions (mm)			Weight (kw)
												Approach	Working	Return	L	W	H	
1311001	40/1500	400	1500	1200	365	220	120	70	720	4	120	60	9.5	60	1750	1165	2110	2850
1311002	40/2200	400	2200	1700	365	220	120	70	720	4	170	60	9.5	60	2300	1165	2110	3350
1311003	50/2500	500	2500	2000	375	220	120	70	720	4	200	60	9.5	60	2600	1165	2110	3650
1311004	63/2500	630	2500	2000	385	250	120	70	780	5.5	200	60	8.5	60	2600	1210	2185	4300
1311005	63/3200	630	3200	2700	385	250	120	70	780	5.5	280	60	8.5	60	3300	1210	2185	5280
1311006	80/2500	800	2500	2000	385	320	120	70	800	5.5	200	60	8.5	80	2600	1385	2225	4680
1311007	80/3200	800	3200	2700	385	320	120	70	800	5.5	280	60	8.5	80	3300	1385	2225	5600
1311008	100/2500	1000	2500	2000	430	350	160	70	850	7.5	400	80	9	70	2600	1565	2500	6800
1311009	100/3200	1000	3200	2700	430	350	160	70	850	7.5	480	80	9	70	3300	1565	2500	7800
1311010	100/4100	1000	4100	3300	430	350	160	70	850	7.5	580	80	9	70	4200	1565	2500	9000
1311011	100/2500D	1000	2500	2000	390	350	160	70	900	7.5	400	80	9	70	2600	1565	2490	7300
1311012	100/3200D	1000	3200	2700	390	350	160	70	900	7.5	480	80	9	70	3300	1565	2490	8500
1311013	100/4100D	1000	4100	3300	390	350	160	70	900	7.5	580	80	9	70	4200	1565	2490	9300
1311014	100/5100D	1000	5100	4400	390	350	160	70	950	7.5	580	80	9	70	5200	1600	2600	125000
1311015	125/2500	1250	2500	2000	390	350	160	70	900	11	400	80	7	70	2600	1660	2500	7800
1311016	125/3200	1250	3200	2700	390	350	160	70	900	11	480	80	7	70	3300	1660	2500	9000
1311017	125/4100	1250	4100	3300	390	350	160	70	900	11	580	80	7	70	4200	1660	2500	10500
1311018	125/5100	1250	5100	4400	390	350	160	70	900	11	580	80	7	70	5200	1700	2900	13800
1311019	160/2500	1600	2500	2000	390	350	160	70	900	11	400	80	9	85	2600	1710	2500	9500
1311020	160/3200	1600	3200	2700	390	350	160	70	900	11	480	80	9	85	3300	1710	2500	10500
1311021	160/4100	1600	4100	3300	390	350	160	70	900	11	580	80	9	85	4200	1710	2500	11800
1311022	160/5100	1600	5100	4400	390	350	160	70	950	11	580	80	9	85	5200	1800	2800	16200
1311023	160/6100	1600	6100	5400	390	350	160	70	1000	11	580	80	9	85	6100	1800	3000	20500
1311030	200/2500	2000	2500	2000	450	400	200	100	910	15	400	80	7	85	2700	1890	2740	11300
1311031	200/3200	2000	3200	2700	450	400	200	100	910	15	480	80	7	85	3300	1890	2740	13000
1311032	200/4100	2000	4100	3300	450	400	200	100	910	15	580	80	7	85	4200	1890	2740	14500
1311033	200/5100	2000	5100	4600	450	400	200	100	990	15	580	80	7	85	5200	1940	2890	20500
1311034	200/6100	2000	6100	5400	450	400	200	100	1050	15	580	80	7	85	6200	1940	3030	24000
1311035	250/2500	2500	2500	2000	450	400	200	100	950	18.5	400	80	9	105	2700	1960	2810	12500
1311036	250/3200	2500	3200	2700	450	400	200	100	950	18.5	480	80	9	105	3420	1960	2810	14000
1311037	250/4100	2500	4100	3300	450	400	200	100	950	18.5	580	80	9	105	4200	1960	2810	16200
1311038	250/5100	2500	5100	4600	450	400	200	100	990	18.5	580	80	9	105	5250	1960	2900	21500
1311039	250/6100	2500	6100	5400	450	400	200	100	1050	18.5	580	80	9	105	6200	1960	3050	24500

1311040	320/3200	3200	3200	2700	520	400	250	150	980	22	520	80	9	60	3400	2100	3100	19100
1311041	320/4100	3200	4100	3300	520	400	250	150	980	22	620	80	9	60	4300	2100	3150	22000
1311042	320/5100	3200	5100	4600	520	400	250	150	1050	22	620	80	9	60	5300	2150	3500	29500
1311043	320/6100	3200	6100	5400	520	400	250	150	1150	22	620	80	9	60	6300	2150	3700	34600